

Aapki Jeet. Hamari Jeet.















Modern, Safe and Ergonomic Interiors

TECHNICAL SPECIFICATIONS	PARTNER (4-TYRE)		PARTNER (6-TYRE)			
	10 ft LB	14 ft LB	11 ft LB	14 ft LB	17ft LB	
WEIGHT						
Gross Vehicle Weight (kg)	6020	6860	7200	7200	7200	
Rated Payload (FSD) (kg)	3386	4081	4446	4346	4141	
LOAD BODY DIMENSIONS						
Load Body Length (mm)	3160	4230	3415	4230	5180	
Load Body Width (mm) (HSD)	1960	2060	2060	2060	2200	
Side Deck Height (mm)	FSD: 460 – HSD: 1840					
POWER TRAIN						
Engine Type	ZD30 Diesel Engine with DDTi (Double Overhead Camshaft, Common Rail, Direct Injection, Turbo Intercooled)					
Displac ement / Cubic Capacity	2953 cc					
Maximum Power Output (in HP)	118 HP @ 2750 RPM (BS4)					
Maximum Torque (Nm)	320 Nm @1350-2600 RPM (BS4)					
Clutch	280 mm Dia, Single Dry Plate, Diaphragm Push Type					
Transmission	Fully Synchromesh 5 - Forward & 1 - Reverse					
Fuel Tank Capacity (litre)	90 litre					
SUSPENSION & TYRES						
Front Suspension	Parabolic with Double Acting Shock Absorbers Parabolic with Double Acting Shock Absorbers					
Rear Suspension	Semi-elliptic with Double Acting Shock Absorbers  Semi-elliptic with Double Acting Shock Absorbers					
No. of Tyres	Front 2, Rear 2, Spare 1 Front 2, Rear 4, Spare 1					
Tyre Size	8.25 x 16-16 PR		7.50 x 16-16 PR			
Loading Platform Height (mm)	1050	1035	1042	1035	1074	
Turning Circle Radius (TCR) (m)	6.2	7.5	5.7	6.75	7.85	
Min. Ground Clearance	238	238	221	221	221	
OVERALL DIMENSIONS						
Wheel Base (mm)	2685	3335	2820	3320	3955	
Overall Length (mm)	4915	5940	5170	5990	6935	
Overall Height (mm)	FSD: 2250	FSD: 2250	FSD :	2240	FSD: 2260	
Overall Height (mm)	HSD: 2770	HSD : 2765	HSD : 2765 HSD : 2690		HSD: 2690	
ELECTRICALS						
Battery	1 x 75 AH					
Alternator	70 A (LS), 90 A (LX)					
STEERING						
Steering System	Power (LS) Power (LS)					
BRAKES						
Service Brake	Dual Circuit Hydraulic with Vacuum Assist and LCRV					
Parking Brake	Transmission mounted, Cable operated					
PERFORMANCE						
Gradeability	18%	18%	28%	28%	26%	
			DARTNER (4 TVRE)		ED (6 TVDE)	

FEATURES		PARTNER (4-TYRE)	PARTNER (6-TYRE)	
		Partner LS	Partner LS	Partner LX
COMFORT & CONVENIENCE	Tiltable Manual Steering	NA	NA	NA
	Tiltable Power Steering	٧	٧	√
	Reclining & Sliding Driver Seats	√	√	√
	Door Handle cum Armrest (Driver & Co-driver)	V	√	√
	Digital Clock (On Instrument Cluster)	√	√	√
	Mobile Charging Point (12V)	√	√	√
	Lockable Glove Box	√	√	√
	Bottle Holder	√	√	√
	Lockable Battery Box	√	√	√
	AC with Heater Unit (HVAC)	X	Х	٧
	Windshield Defogger	X	Х	٧
INTERIORS	Dual Tone Dash Board	√	√	√
	Seat Material - Dual Tone	Vinyl	Vinyl	Fabric
	Moulded Roof & Door Trims	√	√	√
SAFETY	3-point Type ELR Seat Belt	√	√	√
	Fog Lamp Provision	√	√	√
	Vacuum-assisted Brakes with LCRV	√	√	√
TECHNO-LOGY	Tiltable Cabin	√	√	√
	Cable Type Gear Shift	√	√	√
	Low Vacuum in Brake Booster Indicator	√	√	√
	Speed Limiting on ECU	√	√	√
	Provision for Power Take-off (Mechanical)	√	√	√

<sup>\*</sup>Terms and conditions apply. \*Disclaimer: Under standard test conditions. Accessories shown are not a part of the standard equipment. The illustrations, colours shown are indicative only and the actual may vary. Ashok Leyland reserves the right to change specifications/designs without prior permission and notice, without any liability in view of our policy of continuous improvement, Aug 2018.


## **SUPERIOR LOAD CARRYING CAPACITY**



Rated Payload up to 4.6T Options



Low Loading Platform Height






Runner Mounted Load Body

### SUPERIOR MILEAGE



- Proven Japanese technology
- · Powerful and fuel-efficient, ensuring better return on investment
- Comes with 16 valves and DDTi: Double Overhead Camshaft Direct, Injection, Turbo Intercooled, which ensures superior performance




Flat Torque Available over Wide RPM

White Goods

**APPLICATIONS** 

### **HEAVY-DUTY AGGREGATES**







Heavy-Duty Axle



Front Parabolic Suspension and Rear Semi-elliptical Suspension

**FMCG Distribution** 



**Industrial Goods** 

## **CLASS LEADING COMFORT**



Modern Cabin



Safe and Ergonomic Interiors




Tiltable Power Steering



Parcel or Courier


## LOAD BODY LENGTH OPTIONS







14 ft



**LOAD BODY OPTIONS** 



CAB CHASSIS (CBC)





FIXED SIDE DECK (FSD) HIGH SIDE DECK (HSD)

# Reach out to us today!

Email: lcv@ashokleyland.com Web: www.ashokleylandlcv.com Toll-free: 1800 1022 666

Authorised dealer:

## SUITABLE FOR ALL APPLICATIONS

## DAILY NEEDS

Fruits and Vegetables Grocery and FMCG **Food Grains** Beverages Milk Water

Poultry

## INDUSTRIAL NEEDS

Cement Hardware Construction Material Industrial Goods White Goods **Refrigerated Containers** Fertilisers

Textile Furniture LPG Catering Market Load

# BUSINESS NEEDS

**Movers and Packers** Parcel and Courier