

CAUTION: • Do not weld or drill on chassis frame. • Accessories, colour & features as shown in the picture or elsewhere may not constitute to standard fitment. • As a result of continuous research & innovations carried out, specifications are merely indicative & are subject to change without notice.
• Weight mentioned is for standard configuration with standard body size & will change due to optional fitments.

EICHER TRUCKS AND BUSES VE Commercial Vehicles Ltd.

VE Commercial Vehicles Ltd. # 96, Institutional Area, 3rd Floor, Sector 32 Gurgaon-122001, Haryana. TE COMMERCIAL VEHICLES A VOLVO GROUP AND EICHER MOTORS JOINT VENTURE

Registered Office CIN: U74900DL2008PLC175032 3rd Floor Select Citywalk, A-3 District Centre, Saket, New Delhi – 110017, India.

Email - info@vecv.in

Job No: 15100695 Close Size: 29.7 x 21 cm Date: 29.10.15



Page - 24 Page - 1

PARTNERSHIP WITH THE VOLVO GROUP.

Two leading players in the commercial vehicle business joined hands in 2008 with a convergent vision of driving modernization in commercial transportation in India and developing world. Volvo Group, the world's leading manufacturer of trucks, buses, construction equipments and marine and industrial engines, brought its global expertise and world-class technology, while Eicher Motors brought its frugal engineering and deep knowledge of the developing markets. The mission of this joint venture – VE Commercial Vehicles Ltd. is to raise the standard of the commercial transportation industry and take it to a new professional level. Eicher, the flagship brand, is taking the lead in ushering in the future of Indian trucking.

For 30 years, we have maintained a great association with the government.

An association that entitles full support in all of the government endeavors. Working together for a better future, we have given the best of technology and performance to our customers. Walking together hand in hand with the government has taken us to a whole new level. And it's our mutual commitment and dedication that has resulted in our strong partnership.

INDEX

GLOBAL MANUFACTURING PLANT	1-
EICHER LMD SERIES	3-0
EICHER PRO TROOP CARRIER \$	
PRISON VAN SERIES	7-8
EICHER WATER TANKER SERIES	9-10
EICHER BUS SERIES	11-14
EICHER HD SERIES	15-18
■ EICHER NETWORK	19
	 EICHER LMD SERIES EICHER PRO TROOP CARRIER & PRISON VAN SERIES EICHER WATER TANKER SERIES EICHER BUS SERIES EICHER HD SERIES

Page - 2



Page - 4 Page - 5



| LMD SERIES





Eicher Pro **1110XP**

Eicher Pro 1110

GVW	kgs	12976	12976			11950						
Emission Norm		BSIV	BSIV				BSIV					
Engine Type		E494 4	cyl, 4V CF	RS Engine wit	h Volvo G	roup EMS 3	3.0	E494 4 cyl	, 4V CRS Engin	e with Volvo	Group EMS 3.	0
Engine Power		101Kw (~135 HP)	@ 2600 rpm				101Kw (~13	5 HP) @ 2600 r	pm		
Engine Torque		450Nm	@ 1200-	1800 rpm				450Nm @	1200-1800 rpm	l		
Transmission		6 Spee	6 Speed - Eicher 4M6S				6 Speed -	Eicher 4M6S				
Brake		Service	Service: Dual Circuit, full air S cam with VOSS fitment				Service: Dual Circuit, full air S cam with VOSS fitment					
Tyre Size		8.25 x 2	8.25 x 20 - 16 PR			8.25 x 20 - 16 PR						
Wheel Base	mm	38	00	430	0	50	50	3800	430	00	50	50
Cargo Body Length	mm	4431	5252	5805	6100	6776	7357	5252	5805	6100	6776	7357
	ft	14.5	17.2	19	20	22	24	17.2	19	20	22	24
Cargo Body Width	mm	2212	2125	2125/2284	2125	2125	2284	2125	2125/2284	2125	2125	2284
	ft	7.2	7	7 / 7.5	7	7	7.5	7	7 / 7.5	7	7	7.5
Body Options		CBC/FS	CBC/FSD/DSD/HSD				CBC/FSD/DSD/HSD					
Applications		Fire Tru	ıcks/ Muni	cipal				Fire Trucks	/ Municipal			

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.

Page - 6 Page - 7

| LMD SERIES







Eicher Pro **1095XP**

Eicher Pro **1095**

Eicher Pro **1090**

Model		Eicher Pro 1095XP	Eicher Pro 1095	Eicher Pro 1090
GVW	kgs	10700	9500	8720
Emission Norm		BSIV	BSIV	BSIV
Engine Type		E 483 4 cyl 2 V CRS Engine	E 483 4 cyl 2 V CRS Engine	E 483 4 cyl 2 V CRS Engine
Engine Power		80Kw (~110 HP) @ 2600 rpm	80Kw (~110 HP) @ 2600 rpm	80Kw (~110 HP) @ 2600 rpm
Engine Torque		350Nm @ 1200-1800 rpm	350Nm @ 1200-1800 rpm	350Nm @ 1200-1800 rpm
Transmission		5 Speed - Eicher 35M5R	5 Speed - Eicher 35M5R	5 Speed - Eicher 35M5R
Brake		Service: Dual Circuit, full air S cam with APDA unit	Service: Dual Circuit, full air S cam with APDA unit	Service: Hydraulic Brake Vaccum Assisted
Tyre Size		8.25 x 16 - 16 PR	8.25 x 16 - 16 PR	7.50 x 16 - 16 PR
Wheel Base	mm	3515/3765/4065/4265/4265/4765	3515/3765/4065/4760	3515/3765
Cargo Body Length	mm	4315/4960/5346/5804/6104/6626	4315/4960/5346/6626	4315/4960
Cargo Body Length	ft	14.1/16.2/17.6/19/20/21.5	14.1/16.2/17.6/21.5	14.1/16.2
Cargo Body Width	mm	2007/2007/2007/2127/2127/2007	2007	2007
curgo body width	ft	6.6/6.6/6.6/7/7/6.6	6.6	6.6
Body Options		CBC/FSD/DSD/HSD	CBC/FSD/DSD/HSD	CBC/FSD/DSD/HSD
Applications		Fire Trucks/ Municipal	Fire Trucks/ Municipal	Fire Trucks/ Municipal

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.









Eicher Pro **1075**

Eicher Pro 1059

Eicher Pro **1055**

Model		Eicher Pro 1075	Eicher Pro 1059	Eicher Pro 1055
GVW	kgs	7450	6450	6250
Emission Norm		BSIV	BSIV	BSIV
Engine Type		E 483 4 cyl 2 V CRS Engine	E 483 4 cyl 2 V CRS Engine	E 483 4 cyl 2 V CRS Engine
Engine Power		80Kw (~110 HP) @ 2600 rpm	70Kw (~95 HP) @ 2600 rpm	70Kw (~95 HP) @ 2600 rpm
Engine Torque		350Nm @ 1200-1800 rpm	300Nm @ 1200-1800 rpm	300Nm @ 1200-1800 rpm
Transmission		5 Speed - Eicher 35M5R	5 Speed - Eicher 3M5D	5 Speed - Eicher 3M5D
Brake		Service: Hydraulic Brake Vaccum Assisted	Service: Hydraulic Brake Vaccum Assisted	Service: Hydraulic Brake Vaccum Assisted
Tyre Size		7.50 x 16 - 16 PR	8.25 x 16 - 16 PR	7.50 x 16 - 16 PR
Wheel Base	mm	2815/3515/3765/4065	2750/3350	2815
Cargo Body Length	mm	3680/4315/4960/5346	3077/4319	3068
Curyo Bouy Length	ft	12/14.1/16.2/17.6	10/14.1	10
Carro Dody Width	mm	2007	2007	1850
Cargo Body Width	ft	6.6	6.6	6
Body Options		CBC/FSD/DSD/HSD	CBC/HSD	CBC/FSD
Applications		Fire Trucks/ Municipal	Fire Trucks/ Municipal	Fire Trucks/ Municipal

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.

Page - 8



LMD SERIES








STTC

Products		STTC		Prison Van	Eicher Pro HTTC
Model	Pro 1050	Pro 1075	Pro 1095	Pro 1075	Pro 1075
GVW (kg)	5400	7450	9500	7450	7450
Seating Capacity	17	25	29	25	27
Wheel Base (mm)	2750	3515	4065	3515	3765
Emission Norm	BSIV	BSIV	BSIV	BSIV	BSIV
Engine Type	E483 4Cyl 2 V CRS	E483 4Cyl 2V CRS	E483 4Cyl 2V CRS	E483 4Cyl 2V CRS	E483 4Cyl 2V CRS
Engine Power	70Kw (~95 HP) @ 2600 rpm	80Kw (~110HP) @ 2600 rpm			
Engine Torque	300Nm @ 1200-1800 rpm	350Nm @ 1200-1800 rpm			
Transmission	5 Speed - Eicher 3M5D	5 Speed - Eicher 35M5R			
Brake	Hydraulic Brake	Hydraulic Brake	Hydraulic Brake	Hydraulic Brake	Hydraulic Brake
Tyre Size	7.50 x 16 - 16 PR	7.50 x 16 - 16 PR	8.25 x 16 - 16 PR	7.50 x 16 - 16 PR	7.50 x 16 - 16 PR
ABS	Yes	Yes	Yes	Yes	Yes

Prison Van

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.

Page - 10 Page - 11



WATER TANK SERIES









Eicher Pro **1075**

Eicher Pro **1090**

Eicher Pro 1110

Eicher Pro **5016**

Model	Eicher Pro 1075 Water Tanker	Eicher Pro 1090 Water Tanker	Eicher Pro 1110 Water Tanker	Eicher Pro 5016 Water Tanker
GVW (kgs)	7450	8720	11990	16200
Wheelbase (mm)	3515	3515	3800	4300
Water Tanker Capacity (kl)	3.5	5	6	9
Emission	BSIV	BSIV	BSIV	BSIV
Fuel Type	Diesel	Diesel	Diesel	Diesel
Engine Type	E483 4Cyl 2V CRS	E483 4Cyl 2V CRS	E494 4Cyl 4V CRS with volvo group EMS 3.0	E694 5.7 liter with i3 EGR technology
Engine Power	80Kw (~110HP) @ 2600 rpm	80Kw (~110HP) @ 2600 rpm	101Kw (~135HP) @ 2600 rpm	170HP @ 2400 rpm
Engine Torque	350Nm @ 1200-1800 rpm	350Nm @ 1200-1800 rpm	450Nm @ 1200-1800 rpm	620Nm @ 1200-1900 rpm
Transmission	Eicher 35M5R	Eicher 35M5R	Eicher 4MS6	ET706S
Gear Type	5 Speed (5 forward, 1 reverse) with hybrid GSL	5 Speed (5 forward, 1 reverse) with hybrid GSL	6 Speed (6 forward, 1 reverse) with hybrid GSL	6 Speed (6 forward, 1 reverse) with hybrid GSL
Brake	Hydraulic Brake	Hydraulic Brake	Air Brake	Air Brake
Steering	Manual Steering	Manual Steering	Manual Steering	Tilt & telescopic Hydraulic Power Steering
Tyre Size	7.50 x 16 - 16PR	7.50 x 16 - 16PR	8.25 x 20 - 16PR	10R20 16PR

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.

Page - 12 Page - 13



BUS SERIES







Eicher Skyline Pro **3008** (36+1 HHR Seats)

Eicher Skyline Pro **3009** (44+1 HHR Seats)

Eicher Skyline **20.15** (57+1 and 62+1 HHR Seats)

PARAMETERS	Skyline Pro 3008	Skyline Pro 3009	20.15 N Skyline
Wheelbase (mm)(inch)	4330 (171")	5260 (207")	5840 (230") and 5340 (210")
Overall Length (m)	8.923	10.395	11.14 and 10.39
Overall W/ H (mm)	2345/2863	2345/2863	2590/3175
Engine Make	E494 4V CRS BSIV	E494 4V CRS BSIV	E694 4V CRS BSIV EGR
Power	120 HP @ 2600 rpm	120 HP @ 2600 rpm	190 HP @ 2400 rpm
Torque	400 Nm @ 1400-1600 rpm	400 Nm @ 1400-1600 rpm	715 Nm @ 1200-1800 rpm
Transmission Make	ET40S5	ET40S5	ET70S6
Туре	5 speed synchromesh	5 speed synchromesh	6 Speed with overdrive synchromesh
Clutch	310 mm dia with clutch booster	310 mm dia with clutch booster	395 mm dia with clutch booster
Brakes	Dual circuit 'S' cam full air brakes	Dual circuit 'S' cam full air brakes	Dual circuit 'S' cam full air brakes
Tyres	235/75R17.5 - 14 PR Tubeless	235/75R17.5 - 14 PR Tubeless	10R20 - 16 PR
Suspension	Parabolic	Parabolic	Front and Rear weveller suspension
Steering	Power steering, tilt and telescopic	Power steering, tilt and telescopic	Power steering, tilt and telescopic
Fuel Tank Capacity	100 Ltrs	160 Ltrs	250 Ltrs

Chassis version also available in all the bus variants

Page - 14 Page - 15

BUS SERIES




Eicher Starline **12.12 K** (50+1 HHR Seats)



Eicher Starline **10.90 L** (39+1+1 HHR Seats)



Eicher Starline **10.75 H** (31+1+1 HHR Seats)



Chassis version also available in all the bus variants.



Eicher Starline **10.75 E** (23+1+1 HHR Seats)



Eicher Starline **10.50 E**



Eicher Starline **10.50 C** (15+1+1 HHR Seats)

PARAMETERS	10.75 E Starline	10.50 E Starline	10.50 C Starline
Wheelbase (mm)(inch)	3515 (138")	3350 (132")	2750 (108")
Overall Length (m)	6.629	5.905	4.965
Overall W/H (mm)	2160/2770	2125/2750	2125/2750
Engine Make	E483 CRS BSIV	E483 CRS BSIV	E483 CRS BSIV
Power	107 HP @ 2600 rpm	94 HP @ 2600 rpm	94 HP @ 2600 rpm
Torque	350 Nm @ 1200-1800 rpm	300 Nm @ 1200-1800 rpm	300 Nm @ 1200-1800 rpm
Clutch	310 mm dia with clutch booster	275 mm dia	275 mm dia
Transmission Make	ET35S5	ET30S5	ET30S5
Туре	5 Speed synchromesh	5 Speed synchromesh	5 Speed synchromesh
Brakes	Dual circuit 'S' cam full air brakes	Hydraulic brakes	Hydraulic brakes
Tyres	7.50x16 - 16 PR	8.25x16 - 16 PR	8.25x16 - 16 PR
Suspension	Semi-elliptical	Semi-elliptical	Semi-elliptical
Steering	Power steering, tilt and telescopic	Manual, tilt and telescopic	Manual, tilt and telescopic
Fuel Tank Capacity	100 Ltrs	60 Ltrs	60 Ltrs

Chassis version also available in all the bus variants.

BUS SERIES

Page - 16 Page - 17



HD SERIES







Eicher Pro **5025**



Eicher Pro **5031**

Model	Eicher Pro 5016	Eicher Pro 5025	Eicher Pro 5031
GVW (Kgs)	16200	25000	31000
Wheelbase (mm)	4300/4800/5340/6260	4900/5260/6600	5590/6600
Engine Type	E694 5.7 liter CRS with i3 EGR Technology	E694 5.7 liter CRS with i3 EGR Technology	E694 5.7 liter CRS with EGR i3 Technology
Engine Power	170 HP @ 2400 rpm	192 HP @ 2400 rpm	192 HP @ 2400 rpm
Engine Torque	620 Nm @ 1200-1900 rpm	715 Nm @ 1200-1800 rpm	715 Nm @ 1200-1800 rpm
Gearbox	ET70S6, 6 Forward & 1 Reverse	ET90S6, 6 Forward & 1 Reverse	ET90S6, 6 Forward & 1 Reverse
Chassis Type	"C" Channel ladder type frame, 230x76x6 mm	"C" Channel ladder type frame, 285x76x6 mm	"C" Channel ladder type frame, 285x76x6 mm
Brakes	Service Brake: Dual circuit full air "S" cam Parking Brake: Full air hand operated on rear wheels	Service Brake: Dual circuit full air "S" cam Parking Brake: Full air hand operated on rear wheels	Service Brake: Dual circuit full air "S" cam Parking Brake: Full air hand operated on rear wheels
Electricals	24V	24V	24V
Tyres	10R20 - 16PR	10R20 - 16PR	10R20 - 16PR
Variants	CBC \$ FBT - 18 ft/ 20 ft/ 24 ft CWC - 18 ft/ 20 ft/ 24 ft / 32 ft	FBT - 24 ft CBC- 24 ft/ 31 ft CWC - 24 ft/ 32 ft	FBT - 24 ft/ 26 ft CBC- 24 ft/ 26 ft/ 31 ft CWC - 24 ft/ 26 ft/ 32 ft
Application	Fire Trucks/ Municipal	Fire Trucks/ Municipal	Fire Trucks/ Municipal

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.

Page - 18 Page - 19

HD SERIES







Eicher Pro **6031**



Eicher Pro **6037**

Model	Eicher Pro 6025	Eicher Pro 6031	Eicher Pro 6037
Emission Technology	SCR	SCR	SCR
GVW (Kgs)	25000	31000	37000
Wheelbase (mm)	4900/5300/6600	6150/6600	6600
Engine	VEDX5 BSIV	VEDX5 BSIV	VEDX5 BSIV
Engine Power	180 HP @ 2200 rpm	210 HP @ 2200 rpm	210 HP @ 2200 rpm
Engine Torque	750 Nm @ 1200-1600 rpm	825 Nm @ 1200-1600 rpm	825 Nm @ 1200-1600 rpm
Gearbox	ET90S6 (6 Forward, 1 Reverse)	ET90S6 (6 Forward, 1 Reverse)	ZF 9S 1110, (9 Forward, 1 reverse)
Chassis Type	Joggled frame, 285x76x7 mm with 5 mm stiffener	Joggled frame, 285x76x7 mm with 5 mm stiffener	Joggled frame, 285x76x7 mm with 5 mm stiffener
Rear Axle	Fully Floating Banjo type	Fully Floating Banjo type	Fully Floating Banjo type
Brakes	Service brake: Dual circuit full air Parking brake: Pneumatic hand operated	Service brake: Dual circuit full air Parking brake: Pneumatic hand operated	Service brake: Dual circuit full air Parking brake: Pneumatic hand operated
Variants	CWC- 24 ft/ 32 ft CBC- 24 ft/ 31 ft FBT- 24 ft	CWC- 24 ft/ 26 ft/ 28 ft/ 32 ft CBC- 24 ft/ 26 ft/ 28 ft/ 31 ft FBT- 24 ft/ 26 ft/ 28 ft	CWC- 28 ft/ 30 ft CBC- 28 ft/ 30 ft FBT- 28 ft

Along with a completely new Pegasus front look styling across the product family, the new range of vehicles is a quantum leap in each and every aspect of exterior design, engine technology and cabin features.












Eicher Pro **5016T**

Eicher Pro 6025T Eicher Pro 6025T FE Eicher Pro 6025T TM

Model	Pro 5016T BSIV	Pro 6025T BS IV	Pro 6025T FE BS IV	Pro 6025T TM BS IV
Emission Technology	i3 EGR	SCR	SCR	SCR
GVW/ GCW (Kgs.)	16,200	25000	25000	25000
Wheelbase (mm)	3485	4000	4000	4000
Engine Model	E694 5.7 liter with i3 EGR technology	VEDX8 BSIV 7.7 liter 4 valve 6 Cylinder CRS	VEDX5 BSIV 5.1 liter 4 valve 4 Cylinder CRS	VEDX5 BSIV 5.1 liter 4 valve 4 Cylinder CRS
Max. Power	170 HP @ 2400 rpm	220 HP @ 2200 rpm	210 HP@ 2200 rpm	210 HP@ 2200 rpm
Max. Torque	620 Nm @ 1200-1900 rpm	850 Nm @ 1100-1700 rpm	825 Nm @ 1200-1600 rpm	825 Nm @ 1200-1600 rpm
Gearbox	ET70S6 (6 Forward, 1 Reverse)	ZF9S1110 (9 Forward, 1 Reverse)	ET90S6 (6 Forward, 1 Reverse)	ET90S6 (6 Forward, 1 Reverse)
Chassis Type	"C" Channel ladder type frame, 285x76x6 mm	"C" Channel ladder type frame, 285x76x7 mm with 6 mm stiffner	"C" Channel ladder type frame, 2 85x76x7 mm with 5 mm stiffner	"C" Channel ladder type frame, 285x76x7 mm with 5 mm stiffner
Brakes	Service Brake: Dual circuit full air "S" cam Parking Brake: Full air hand operated on rear wheels	Service Brake: Dual circuit full air "S" cam Parking Brake: Pneumatic hand operated on rear wheels	Service Brake: Dual circuit full air "S" cam Parking Brake: Pneumatic hand operated on rear wheels	Service Brake: Dual circuit full air "S" cam Parking Brake: Pneumatic hand operated on rear wheels
Front Suspension	Front: Semi elliptic laminated leaf spring with shock absorber Rear: Semi elliptic laminated leaf spring with helper leaf spring	Front: Parabolic leaf springs Rear: Bogie suspension inverted U bolts	Front: Parabolic leaf springs Rear: Semi elliptic multi leaf spring	Front: Parabolic leaf springs Rear: Semi elliptic multi leaf spring
Gradeability	35. 0%	42.5% (crawler gear)	28.6%	25.7% with PTO; 28.6% W/O PTO
Fuel Tank	220L	220L	220L	220L
Variants (Body Size)	CBC & FBT-8.5 CuM, 10 CuM Box	14 CuM, 16 CuM Box; 14 CuM Rock	14 CuM Box	6-7 CuM

Page - 20 Page - 21

EICHER NETWORK







- 152 Authorized Dealerships.
- 270 Workshops with Trained Manpower.
- 120 Eicher Genuine Parts Shoppe.
- 2500 Retailers.

Eicher has an extensive service reach and no matter where you are, Eicher service is never too far away. Eicher has wide and expanding authorized contact points across the country with professionally trained dealership service teams ensuring your vehicle is in safe hands. Eicher dealers are equipped with mobile service vans and 24x7 helpline numbers to ensure quick response. What's more, Eicher genuine parts made to exact specifications are economical and widely available across Eicher dealers, service centres, spare distributors and other outlets.

