

[GO PRO](#)[PROVENANCE](#)[PROGRESS](#)[PROFESSIONAL](#)[PROMISE](#)[PROSPERITY](#)[PROGRAMS](#)[EICHER TRUCK AND BUSES](#) > [PROFESSIONAL](#) > [TRUCKS](#) > [PRO-SERIES](#) > [EICHER PRO 6025T FE](#)

CV
COMMERCIAL VEHICLE
AWARDS 2018

Eicher Pro 6025T wins CV Award in 25 Ton Tipper Category

MCV Cargo Carrier of the Year

PRO SERIES**EICHER PRO 6025T FE**

SELECT MODEL



1000 SERIES (4.9 - 15 TONS)

3000 SERIES (12 - 16 TONS)

5000 SERIES (16 - 40 TONS)

6000 SERIES (25 - 40 TONS)

8000 SERIES (25 - 49 TONS)

VEHICLE FINDER

Series

Vehicle Type

GVW

Application type

DEALER LOCATER

To view the wide spread network of eicher

Show

FINANCIAL SERVICES

Eicher Pro 6025T FE is the Next Gen 25 ton GVW tipper all set to redefine the trucking experience with its unmatched overall performance. Equipped with the highly fuel efficient 5.1 litre CRS engine based on Selective Catalytic Reduction (SCR) technology - designed in association with Volvo Group and a Next Gen cabin with state-of-the-art features, the Eicher Pro 6025T FE creates a benchmark for performances, reliability and higher productivity and hence leads to higher profitability for its owner.

USPs

- ✦ Best in class fuel efficiency
- ✦ Superior uptime
- ✦ Faster turnaround time, quick pick up and acceleration
- ✦ High reliability and durability
- ✦ Unmatched cabin comfort with state of the art features
- ✦ Optimized maintenance cost

APPLICATIONS

- Aggregate Transportation
- Road Construction
- Sand Transportation
- Secondary Transportation of Coal/Iron Ore

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE DESCRIPTION
GVW	25000 Kgs.

Avail of professional financing solutions to ensure your Eicher commercial vehicle starts quickly delivering profitability to your business.

[/ MORE](#)

Wheelbase	4000mm
Engine	VEDX5, BS IV Engine w ith SCR technology
Max Pow er	210HP @ 2200 rpm
Max. Torque	850Nm @ 1100 - 1700rpm
Gear Box	ET90S6(6 Forw ard,1 Reverse)
Clutch Size and Type	395 mm, Pull type booster assisted
Front Axle	ETB Wider Track Axle
Rear Axle	Meritor Tandem - Fully floating banjo type
FDR	6.16
Chassis	Domex 650, 285x76x7 mm w ith 5 mm stiffener
Brakes	Service brake: Dual Circuit Full air,'S' cam
	Parking brake: Pneumatic hand operated
Steering	Tilt and Telescopic hydraulic pow er steering
Front Suspension	Parabolic leaf springs
Rear Suspension	Semi- elliptical multi leaf spring
Max Speed	60 km/hr
Gradeability	29.6%
Ground Clearance	285 mm
Fuel Tank	220 lts.

Urea Tank	22 lts.
Electricals	2 x 24 V (150 Ah)
Tyre	11 X 20 Cross Ply
Tipping Kit	Hyva FE 129-3-3640
Body Options	14 Cum Box only