



296NM @ 1500 ± 50RPM



GVW

6.44 TON



POWER

100.5BHP @ 2800RPM

SML ISUZU PRISON VAN BS-IV 3335/FBV/ PRISON VAN

Engine Displacement Off-road Gradeability Maximum Speed

3455 cc - - -

Maximum Power Gross Vehicle Weight (GVW) Axle Configuration

100.5bhp @ 2800rpm 6.44 ton 4x2



GET PRICE QUOTE

TECHNICAL SPECIFICATIONS OF SML ISUZU PRISON VAN BS-IV 3335/FBV/ PRISON VAN

PERFORMANCE		DESIGN & BUILD		COMFORT		SAFETY	
Engine	CRDi	Body Option	Box Body	Steering Me	chanical Steering	Brakes	Hydraulic Brakes
Emission Norms	BS-IV	Chassis Type	Chassis with Cabin	A/C	×	Front Axle	×
Engine Cylinders	×	Cabin Type	Day Cabin	Cruise Control	×	Front Suspension	×
Displacement (cc)	3455	Tiltable Cabin	×	Navigation System	×	Rear Axle	×
Max Power 1	00.5bhp @ 2800rpm	Axle Configuration	4x2	Driver Information Display	×	Rear Suspension	×
Max Torque 296N	lm @ 1500 ± 50rpm	Front Tyre	7.50 x 16 -16 PR	Telematics	×	ABS	×
Transmission	Manual	Rear Tyre	7.50 x 16 -16 PR	Adjustable Driver Seat	×	Parking brakes	×
Clutch	×	Wheelbase (mm)	3335	Tiltable Steering	×	Power Steering	Optional
Gearbox	×	Overall Length (mm)	5954	Arm-rest	×	Fog Lights	×
Fuel Tank (Litres)	90	Overall Width (mm)	2200	Seat type	×	Tubeless Tyres	×
Gradeability (%)		Overall Height (mm)	×	× OTHERS		Seat belts	×
Turning Radius (mm)	×	Ground Clearance (mm)	×	· · · · · · · · · · · · · · · · · · ·		Hill Hold	×
Max Speed (km/h)	×	GVW / GCW (Kgs)	6440	Body Brakes Hydraulic Vacuum assisted			
		Kerb Weight (Kgs)	×				
		Payload (Kgs)	×				

