



SML ISUZU

RECOVERY VAN BS-IV

[GET PRICE QUOTE](#)

KEY SPECIFICATIONS



TORQUE

296NM @ 1500 ± 50RPM



GVW

-



POWER

100.5BHP @ 2800RPM

SML ISUZU RECOVERY VAN BS-IV 2515/FBV/RECOVERY VAN

Engine Displacement
3455 cc

Off-road Gradeability

-

Maximum Speed

-

Maximum Power
100.5bhp @ 2800rpm

Gross Vehicle Weight (GVW)

-

Axle Configuration
4x2



[GET PRICE QUOTE](#)

TECHNICAL SPECIFICATIONS OF SML ISUZU RECOVERY VAN BS-IV 2515/FBV/RECOVERY VAN

PERFORMANCE		DESIGN & BUILD		COMFORT		SAFETY	
Engine	Mech	Body Option	Box Body	Steering	Mechanical Steering	Brakes	Hydraulic Brakes
Emission Norms	BS-IV	Chassis Type	Chassis with Cabin	A/C	×	Front Axle	×
Engine Cylinders	×	Cabin Type	Day Cabin	Cruise Control	×	Front Suspension	×
Displacement (cc)	3455	Tiltable Cabin	×	Navigation System	×	Rear Axle	×
Max Power	100.5bhp @ 2800rpm	Axle Configuration	4x2	Driver Information Display	×	Rear Suspension	×
Max Torque	296Nm @ 1500 ± 50rpm	Front Tyre	7.50 x 16 -16 PR	Telematics	×	ABS	×
Transmission	Manual	Rear Tyre	7.50 x 16 -16 PR	Adjustable Driver Seat	×	Parking brakes	×
Clutch	×	Wheelbase (mm)	2515	Tiltable Steering	×	Power Steering	Optional
Gearbox	×	Overall Length (mm)	4489	Arm-rest	×	Fog Lights	×
Fuel Tank (Litres)	90	Overall Width (mm)	2000	Seat type	×	Tubeless Tyres	×
Gradeability (%)	×	Overall Height (mm)	2070	OTHERS		Seat belts	×
Turning Radius (mm)	×	Ground Clearance (mm)	×	Body Brakes	Hydraulic Vacuum assisted	Hill Hold	×
Max Speed (km/h)	×	GVW / GCW (Kgs)	×				
		Kerb Weight (Kgs)	×				
		Payload (Kgs)	×				