

TATA MOTORS
Connecting Aspirations



Presenting the new TATA YODHA ECO

Bharosa Har Kadam



The reliable pickup
for your business



TECHNICAL SPECIFICATIONS

ENGINE

Type	TATA 4SP CR TCIC 4-cylinder BS4
Capacity	2 956 cc
Max. Output	64 kW (85 hp) @ 3 000 r/min
Max. Torque	250 Nm @ 1 000 - 2 000 r/min
Fuel Tank Capacity	45 l

CLUTCH & TRANSMISSION

Clutch	Single Plate Dry Friction Type 260 mm dia
Gearbox	GBS76 - 5 / 4.1
Steering	Synchromesh, 5 Forward + 1 Reverse
	Power Steering

SUSPENSION

Front	Semi-elliptical Leaf Springs - 6 Leaves
Rear	Innovative Two-stage Semi-elliptical Leaf Springs - 9 Leaves
Anti-roll Bar	Front

BRAKES

Front	Hydraulic, Twin-pot Disc Brakes
Rear	Drum Brakes

WHEELS & TYRES

Tyre	215 / 75 R 16 Radial
Rim Size	16"

OVERALL VEHICLE DIMENSIONS

Width	1 860 mm
Length	5 350 mm
Height	1 810 mm
Ground Clearance	210 mm
Wheelbase	3 150 mm
Internal Load Body (L x B)	2 550 mm (8.4 ft) x 1 703 mm (5.6 ft)
Turning Circle Radius	6 250 mm

WEIGHT

GVW	2 950 kg
Kerb Weight	1 810 kg
Payload	1 140 kg

PERFORMANCE

Gradeability	30 %
Restart Gradeability	22 %
Top Speed	80 km/h
Seating Capacity	D + 1

WARRANTY TERMS

Engine Oil Change Interval	20 000 km
Warranty (On Driveline)	3-year or 3 lakh km (Whichever is earlier)



Flat bed type driver resting seats



Powerful & fuel efficient 3 l bigger engine



Wide load body for higher earnings



Strong front & rear suspension with added leaves



High ground clearance



Warranty 3-year or 3 lakh kmh (Whichever is earlier)



Mileage: 14.06 km/l**



Cabin chassis variant available

TATA MOTORS

SAMPOORNA SEVA

AAPKE SAATH HAR KADAM

TOLL FREE 1800 209 7979

TATA MOTORS INSURANCE

LOYALTY REWARDS

TATA DELIGHT

TATA OK

TATA GENUINE PARTS

TATA SURAKSHA

TATA PROLIFE

TATA KAVACH

TATA MOTORS

For more information, contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400 093. Call: **1800 209 7979** (toll-free), Visit: www.pickup.tatamotors.com or SMS*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

*As per terms & conditions in the operator's service manual.
 *₹ 3 per SMS or as per service provider. ** As per VRDE (Standard Test Conditions)

TATA MOTORS
Connecting Aspirations



Presenting the new TATA YODHA

Bharosa Har Kadam



The reliable pickup
for your business



TECHNICAL SPECIFICATIONS

ENGINE

Type	TATA 4SP CR TCIC 4-cylinder BS4
Capacity	2 956 cc
Max. Output	64 kW (85 hp) @ 3 000 r/min
Max. Torque	250 Nm @ 1 000 - 2 000 r/min
Fuel Tank Capacity	45 l

CLUTCH & TRANSMISSION

Clutch	Single Plate Dry Friction Type 260 mm dia
Gearbox	GBS76 - 5 / 4.1
	Synchromesh, 5 Forward + 1 Reverse
	Power Steering

Steering

SUSPENSION

Front	Semi-elliptical Leaf Springs - 6 Leaves
Rear	Innovative Two-stage Semi-elliptical Leaf Springs - 9 Leaves
	Front

BRAKES

Front	Hydraulic, Twin-pot Disc Brakes
Rear	Drum Brakes

WHEELS & TYRES

Tyre	215 / 75 R 16 Radial
Rim Size	16"

OVERALL VEHICLE DIMENSIONS

Width	1 860 mm
Length	5 350 mm
Height	1 810 mm
Ground Clearance	210 mm
Wheelbase	3 150 mm
Internal Load Body (L x B)	2 550 mm (8.4 ft) x 1 750 mm (5.7 ft)
Turning Circle Radius	6 250 mm

WEIGHT

GVW	3 100 kg
Kerb Weight	1 850 kg
Payload	1 250 kg

PERFORMANCE

Gradeability	30 %
Restart Gradeability	22 %
Top Speed	80 km/h
Seating Capacity	D + 1

WARRANTY TERMS

Engine Oil Change Interval	20 000 km
Warranty (On Driveline)	3-year or 3 lakh km (Whichever is earlier)



Flat bed type driver resting seats



Powerful & fuel efficient 3 l bigger engine



Wide load body for higher earnings



Strong front & rear suspension with added leaves



High ground clearance



Warranty 3-year or 3 lakh km (Whichever is earlier)



Mileage: 14.06 km/l**

TATA MOTORS

SAMPOORNA SEVA

AAPKE SAATH HAR KADAM

TOLL FREE 1800 209 7979

TATA MOTORS INSURANCE

LOYALTY REWARDS

TATA DELIGHT

TATA OK

TATA GENUINE PARTS

TATA SURAKSHA

TATA PROLIFE

TATA KAVACH

TATA MOTORS

For more information, contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: **1800 209 7979** (toll-free), Visit: www.pickup.tatamotors.com or SMS*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

*As per terms & conditions in the operator's service manual.
 *₹ 3 per SMS or as per service provider. ** As per VRDE (Standard Test Conditions)

TATA MOTORS
Connecting Aspirations



Presenting the new TATA YODHA 1500

Bharosa Har Kadam



The reliable pickup
for your business



TECHNICAL SPECIFICATIONS

ENGINE

Type	TATA 4SP CR TCIC 4-cylinder BS4
Capacity	2 956 cc
Max. Output	64 kW (85 hp) @ 3 000 r/min
Max. Torque	250 Nm @ 1 000 - 2 000 r/min
Fuel Tank Capacity	45 l

CLUTCH & TRANSMISSION

Clutch	Single Plate Dry Friction Type 260 mm dia
Gearbox	GBS76 - 5 / 4.1
	Synchromesh, 5 Forward + 1 Reverse
	Power Steering

STEERING

SUSPENSION

Front	Semi-elliptical Leaf Springs - 6 Leaves
Rear	Innovative Two-stage Semi-elliptical Leaf Springs - 9 Leaves
	Front

BRAKES

Front	Hydraulic, Twin-pot Disc Brakes
Rear	Drum Brakes

WHEELS & TYRES

Tyre	215 / 75 R 16 Radial
Rim Size	16"

OVERALL VEHICLE DIMENSIONS

Width	1 860 mm
Length	5 350 mm
Height	1 810 mm
Ground Clearance	210 mm
Wheelbase	3 150 mm
Internal Load Body (L x B)	2 550 mm (8.4 ft) x 1 750 mm (5.7 ft)
Turning Circle Radius	6 250 mm

WEIGHT

GVW	3 350 kg
Kerb Weight	1 850 kg
Payload	1 500 kg

PERFORMANCE

Gradeability	30 %
Restart Gradeability	22 %
Top Speed	80 km/h
Seating Capacity	D + 1

WARRANTY TERMS

Engine Oil Change Interval	20 000 km
Warranty (On Driveline)	3-year or 3 lakh km (Whichever is earlier)



Flat bed type driver resting seats



Powerful & fuel efficient 3 l bigger engine



Wide load body for higher earnings



Strong front & rear suspension with added leaves



High ground clearance



Warranty 3-year or 3 lakh km (Whichever is earlier)



Mileage: 14.06 km/l**

TATA MOTORS

SAMPOORNA SEVA

AAPKE SAATH HAR KADAM

TOLL FREE 1800 209 7979

TATA MOTORS INSURANCE

LOYALTY REWARDS

TATA DELIGHT

TATA OK

TATA GENUINE PARTS

TATA SURAKSHA

TATA PROLIFE

TATA KAVACH

TATA MOTORS

For more information, contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: **1800 209 7979** (toll-free), Visit: www.pickup.tatamotors.com or SMS*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

*As per terms & conditions in the operator's service manual.
 *₹ 3 per SMS or as per service provider. ** As per VRDE (Standard Test Conditions)

TATA MOTORS
Connecting Aspirations



Presenting the new TATA YODHA CREW CABIN

Bharosa Har Kadam



The reliable pickup for your business

TECHNICAL SPECIFICATIONS

ENGINE

Type	TATA 4SP CR 4-cylinder BS4
Capacity	2 956 cc
Max. Output	64 kW (85 hp) @ 3 000 r/min
Max. Torque	250 Nm @ 1 000 - 2 000 r/min
Fuel Tank Capacity	45 l

CLUTCH & TRANSMISSION

Clutch	Single Plate Dry Friction Type 260 mm dia
Gearbox	GBS 76 - 5 / 4.1
	Synchromesh, 5 Forward + 1 Reverse
	Power Steering

Steering

SUSPENSION

Front	Rigid Suspension with Leaf Spring & Shock Absorber
Rear	Semi-elliptical Type with Hydraulic Double Acting Telescopic Shock Absorber
Anti-roll Bar	Front

BRAKES

Front	Hydraulic, Twin-pot Disc Brakes
Rear	Drum Brakes

WHEELS & TYRES

Tyre	215 / 75 R 16 Radial Tubeless
Rim Size	16"

OVERALL VEHICLE DIMENSIONS

Width	1 860 mm
Length	5 350 mm
Height	1 810 mm
Ground Clearance	210 mm
Wheelbase	3 150 mm
Internal Load Body (L x B)	1 780 mm (5.84 ft) x 1 750 mm (5.74 ft)
Turning Circle Radius	6 250 mm

WEIGHT

GVW	2 950 kg
Kerb Weight	1 930 kg
Payload	1 020 kg

PERFORMANCE

Gradeability	30 %
Restart Gradeability	22 %
Top Speed	80 km/h
Seating Capacity	D + 4

WARRANTY TERMS

Engine Oil Change Interval	20 000 km
Warranty (On Driveline)	3-year or 3 lakh km (Whichever is earlier)



STYLING
Aerodynamic design
& trendy decals



DASHBOARD
Car-like utility dashboard
with power steering



FLAT LOAD BODY
1 780 mm (5.84 ft) x
1 750 mm (5.74 ft)



BETTER SERVICEABILITY
Spacious engine compartment
for ease of maintenance



ENGINE
Powerful & fuel efficient
3 l bigger engine



STRONG SUSPENSION
LEAVES
Front - 6, rear - 9



SEATING
Flat bed type
driver resting seats



REAR SEAT
Comfortable rear seat
with more leg room



Mileage: 14.06 km/l**



Non-AC variant

TATA MOTORS

SAMPOORNA SEVA

AAPKE SAATH HAR KADAM

TOLL FREE 1800 209 7979

TATA MOTORS INSURANCE

LOYALTY REWARDS

TATA DELIGHT

TATA OK

TATA GENUINE PARTS

TATA SURAKSHA

TATA PROLIFE

TATA KAVACH

TATA MOTORS

For more information, contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: **1800 209 7979** (toll-free), Visit: www.pickup.tatamotors.com or SMS*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

*As per terms & conditions in the operator's service manual.
** ₹ 3 per SMS or as per service provider. ** As per VRDE (Standard Test Conditions)

TATA MOTORS
Connecting Aspirations



Presenting the new TATA YODHA 4x4

JEET LO HAR MANZIL



TECHNICAL SPECIFICATIONS

ENGINE

Type	Tata 4SPCR TCIC 4-cylinder
Capacity	2 956 cc
Max. Output	64 kW (85 hp) @ 3 000 r/min
Max. Torque	250 Nm @ 1 000 - 2 000 r/min
Fuel Tank Capacity	45 l

CLUTCH & TRANSMISSION

Clutch	Single Plate Dry Friction Type 260 mm dia
Gearbox	GBS76 - 5 / 4.1, 4x4 Mechanical Transfer Shift
Steering	Synchromesh, 5 Forward + 1 Reverse
	Power Steering

SUSPENSION

Front	Semi-elliptical Leaf Springs - 6 Leaves
Rear	Innovative Two-stage Semi-elliptical Leaf Springs - 7 Leaves
Anti-roll Bar	Front

BRAKES

Front	Hydraulic, Disc Brakes
Rear	Drum Brakes

WHEELS & TYRES

Tyre	195 R 15 LT Radial Tube Type
Rim Size	15"

OVERALL VEHICLE DIMENSIONS

Width	1 860 mm
Length	5 005 mm
Height	1 810 mm
Ground Clearance	190 mm
Wheelbase	2 825 mm
Internal Load Body (lxb)	2 227 mm (7.3 ft) x 1 703 mm (5.6 ft)
Turning Circle Radius	5 750 mm

WEIGHT

GVW	2 870 kg
Kerb Weight	1 830 kg
Payload	1 040 kg

PERFORMANCE

Gradeability	55 %
Restart Gradeability	42 %
Top Speed	80 km/h
Seating Capacity	D + 1

WARRANTY TERMS

Engine Oil Change Interval	20 000 km* (10 000 km for hilly terrain)
Warranty (On Driveline)	3-Year or 3 Lakh km (whichever is earlier)



Power steering



Powerful & fuel efficient
3 l bigger engine



Wide load body
for high earnings



Strong front & rear
suspension with added leaves



High ground clearance



Gearbox
Multi terrain capability

4x2 4x2 model available



Warranty 3-Year or
3 Lakh km
(whichever is earlier)



TATA MOTORS

For more information contact: Tata Motors Limited, 4th Floor, CVBU, Ahura Centre, Mahakali Caves Road, Shanti Nagar, Andheri (E), Mumbai - 400093. Call: 1800 209 7979 (toll-free), Visit: www.pickup.tatamotors.com or SMS*: <YODHA> to 5616161.

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

*As per terms & conditions in the operator's service manual. **As per VRDE (Standard Test Conditions)