

Descriptions	LPK 912 BSIV
Descriptions	LFK 912 DOIV
Engine Model	TATA 497 TCIC CR
Engine Type	4 Cylinder in Line Water Cooled Direct Injection Diesel Engine With Intercooler
Fuel Injection Pump	Inline Type With Double Plunger & Double Cab Lobe (CB 18 MICO)
Power	92 kW (125 PS) @ 2400 r/min
Torque	400 Nm @ 1300-1600 r/min
Clutch Type & Dia	Single Plate Dry Friction Type, 310 mm
Gearbox	GBS-40 (5F + 1R Synchromesh)
Suspension	Front & Rear: Semi-elliptical Leaf Spring
Tyres	8.25 - 16 PR Fr Rib
	8.25 - 16 PR Rr Lug
Steering Type	Hydraulic Power Assisted, Tilt & Telescopic (20.4:1 - RANE)
Brakes Type	Dual Circuit Full Air S-Cam Brake
Ground Clearance	217 mm
Max. Speed	80 km/h
Gradeability	40.0%
GVW	9600 kg
FAW	3375 kg
RAW	6225 kg
Front Axle	Heavy Duty Forged I Beam, Reverse Elliot Type
Rear Axle	Single Reduction Hypoid Gears, Fully Floating Axle Shafts (4.857:1)
Battery	12 V - 100 Ah
Fuel Tank Capacity	100
Emission	BSIV
	Dimensions
	FULLY BUILT CAB
WB	2700 mm
TCD	14800 mm
Variants	Fully Built Vehcile (FBV), Cab Chasis
FBV Loading Length	3260 mm (10.7)
FBV (L x W x H)	3260 mm x 2035 mm x 700 mm (272 x 170 x 2.30)
FBV Loading Volume	4.6 Cu.M.
Tipping Angle	53 degree
Warranty	3 Years or 3 Lakh km, Whichever is Earlier, on all Aggregates

## **Advantages**

















You can also contact our Sales Office: Tata Motors Limited, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC, Andheri (East), Mumbai 400093 or call toll-free no. 18002097979.

**CAUTION:** Do not weld or drill on chassis frame • Accessories shown in the picture or elsewhere do not constitute standard fitments. • The specifications are indicative. Due to continuous product improvements, these specifications are liable to change without notice.

For more information, please visit our website: www.tatamotors.com.

\*Terms & conditions apply

## **Dealer stamp**